DuraSeal®

Premium Wood Finishes®

From the trusted DuraSeal® brand

PREMIUM POLYURETHANE+

Rollable floor finish

Everything Pros love about rollable floor finish is here from the definitive name in premium wood finishes.

For decades, professionals have turned to heavy-duty, oil-based, rollable products for the jobs where only the toughest finishes would do. Today, rollable, premium-formula technology finds its place within the DuraSeal family of professional products.



Visit **duraseal.com** for more details.



FOR PROFESSIONAL USE ONLY

PREMIUM POLYURETHANE+

Rollable floor finish

Professional-focused products

DuraSeal® knows its audience: the flooring professional. That's why it was important to bring a **premium, oil-based** and **ROLLABLE finish** to the shelves and into professional hands. It applies easily with a clear, protective finish, yet stands the test of time.

- **Rollable formula for professional application and large area coverage**
- **Oil-based, premium finish**
- **Available in Satin, Semi-Gloss and Gloss**
- **Exceptionally high polyurethane resin content assures maximum durability over time**
- **Remarkable resistance to chipping, peeling, soaps, detergents, water, pets, fruit acids, ink, alcohol, etc.**
- **Especially suitable for use on virtually all interior surfaces, finished or unfinished**
- **Applies easily on wood floors, doors, cupboards, paneling, trim, cabinets, furniture, built-ins, etc.**

SUPERIOR PROTECTION

TRUSTED FABULON® TECHNOLOGY

LONG-LASTING MAXIMUM DURABILITY

MADE IN THE USA SINCE 1898

Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings.

@durasealwoodfinishes

SHEEN	PRODUCT #	SIZE	CASE QTY
Satin	00P835613-44	QT	4
Semi-Gloss	00P835611-44	QT	4
Gloss	00P835610-44	QT	4
Satin	00P835613-16	1 Gallon	4
Semi-Gloss	00P835611-16	1 Gallon	4
Gloss	00P835610-16	1 Gallon	4
Satin	00P835613-20	5 Gallon	1
Semi-Gloss	00P835611-20	5 Gallon	1

Sand and prepare floor according to NWFA-recommended methods. For preparation and application instructions, please see product data sheet.

PHYSICAL PROPERTIES

Color	Amber
Solids	38% by volume & 45% by weight per PV
Viscosity	30 seconds/Ford cup
Coverage	500 sq. ft./gallon
Number of Coats	2 to 3
Leveling	Excellent
Defoaming	Excellent
VOC	<550
Dry Film Thickness	1.5-1.75 mil/coat
Freeze/Thaw Stable	Yes
Shelf Life	36-60 months
Cleanup	Mineral spirits
Storage	Maximum 120 ˚F
Working Temperature	Minimum 50 ˚F
Applicator	T-bar, roller, brush or lambswool
Dry Time (@ 77 ˚F and 50% relative humidity)	
Recoat	8 hours
Foot Traffic	Overnight
Return to Service	3 days
Full Cure	30 days
Furniture and Rugs	30 days
Gloss Level (@ 60)	
Satin	20
Semi-Gloss	50
Gloss	85

DuraSeal® Premium Wood Finishes®

#A103729PD
duraseal.com • 800-364-1359
Please see website to download most recent product data sheet.
© DuraSeal 03/24 DRSL 223/24 A